

Item Number HSR-130R Series Contact Form A Switch Configuration SPST Rev. E

**Form A Offset Gap Switch**

Features	Advantages
<ul style="list-style-type: none"> <li>Hermetically sealed contacts</li> <li>Switch materials are Lead free and RoHS compliant</li> </ul>	<ul style="list-style-type: none"> <li>Extended operations in extreme environments</li> <li>Not ESD sensitive</li> </ul>

**Electrical Specifications**


Power		Watts - maximum	25
Voltage	Switching	VDC - maximum	150
	Breakdown	VDC - minimum	700
Current	Switching	Amp - maximum	1.0
	Carry	Amp - maximum	6.6
Resistance	Initial Contact Resistance	Ohm - maximum	0.10
	Insulation Resistance	Ohm - minimum	1 E11
Capacitance	Contact	pF - typical	0.9
Temperature	Operating	°C	-40 to +125
	Storage	°C	-40 to +200

**Magnetic Specifications**

Pull - In Range		Ampere Turns	40-80
Test Coil		NARM RS-421-A	Coil III

**Physical/Operational Specifications**

Capsule Volume	Excluding Leads	CC - nominal	0.7
Contact Material			Rhodium
Operate Time	Including Bounce	mSeconds - maximum	3.00
Release Time		mSeconds - maximum	2.00



**Notes:**

- Specifications are not constant across entire magnetic range.
- Customer must exercise care in handling, mounting, lead forming, and cutting to prevent damage to glass capsule and/or switch sensitivity.
- For information about performance, custom configurations, mounting options or packaging contact our Sales department.
- Information contained hereon is for informational purposes only and should not be deemed as accurate for a specific application. Consult factory for specific application information and/or latest revision.